

SECURITY SYSTEMS | SSG-100L SLIDING SPEED GATE TURNSTILE (LONG FLAP)

SSG-100L



GENERAL DESCRIPTION

Optima sliding speed gates provide aesthetic and effective control of entry or exit at kinds of toll collection systems like train/metro stations, and access control for commercial centers, stadiums, schools, government and private sector buildings etc.

SYSTEM SPECIFICATIONS

- ⇒ Main body and lateral lids are AISI 304-grade stainless steel.
- ⇒ Top cover tempered glass.
- ⇒ Lateral covers are removable for easy maintenance.
- ⇒ Motor start and stop control is maintained by Optima PLC controller.
- ⇒ Low power consumption and silent running.
- ⇒ Compatible with all Access Control Systems.
- ⇒ Turnstile is equipped with an alarm system which senses forbidden and reverse direction passing.
- ⇒ Turnstiles closes flaps by itself after adjusted time if a valid card is presented but person not passed.
- ⇒ All the obstacles in the passage are sensed with photoelectric sensors. Indoor use only.
- ⇒ Indoor use only.

SECURITY SYSTEMS | SSG-100L SLIDING SPEED GATE TURNSTILE (LONG FLAP)

OPTIONAL ACCESSORIES

- ⇒ Push button box.
- ⇒ Logo print on the flaps.
- ⇒ Card reader system.
- ⇒ Digital Counter.
- ⇒ Card reader mounting plate inside or on the turnstile.
- ⇒ Card reader mounting plate with pedestal.
- ⇒ Stainless steel railing.
- ⇒ Uninterrupted power supply (UPS).
- ⇒ SCADA or any control system: It is possible to change and check the position of turnstile with touch screen control panel, mobile devices (ios-android), computer, etc.

ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

Between -15°C and +65°C, 95% non-condensing humidity; 220-240 VAC, mono phase, 50-60 Hz.

MAIN BODY MEASUREMENTS

